

LUKOIL GENESIS SPECIAL C2 5W-30

low-ash, synthetic high performance engine oil

APPROVALS

MEETS REQUIREMENTS

API SN
ACEA C2
ACEA A1/B1, A5/B5
PSA B71 2290
Renault RN 0700
Fiat 9.55535-S1/S3

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C2 5W-30 is a low-ash, synthetic high performance engine oil, specially developed for up-to-date PEUGEOT, CITROËN, HONDA and TOYOTA gasoline and diesel engines with particulate filter. The new midSAPS technology protects the environment as well as the particulate filter because of the low content of sulphated ash, phosphor and sulphur.

LUKOIL GENESIS SPECIAL C2 5W-30 minimized oil related emissions and guarantees maximum protection of the environment.

LUKOIL GENESIS SPECIAL C2 5W-30 midSAPS technology provide lowest stress and long durability of particulate filter.

LUKOIL GENESIS SPECIAL C2 5W-30 reduced high temperature high shear viscosity stands for maximum fuel economy.

LUKOIL GENESIS SPECIAL C2 5W-30 excellent cold flow properties guarantee quick lubrication of the complete engine and reduces wear, especially during warm-up phase.

APPLICATION

LUKOIL GENESIS SPECIAL C2 5W-30 is a special developed product for up-to-date PEUGEOT, CITROËN, HONDA and TOYOTA gasoline and diesel engines with particulate filter. Warning! This oil may be unsuitable for use in some engines. Consult owner manual or handbook if in doubt.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL C2 5W-30
Density/15°C	kg/m ³	DIN 51575	848
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	5W-30
Viscosity/40°C	mm ² /s	DIN 51562/T1	59,4
Viscosity/100°C	mm ² /s	DIN 51562/T1	10,4
Viscosity index	---	DIN ISO 2909	165
Pour point	°C	DIN ISO 3016	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

1 September 2016, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy +43(1)205 222-8800
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria www.lukoil-lubricants.eu

member of::

